



## Safety Data Sheet

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	26-9520-3	<b>Version Number:</b>	6.01
<b>Issue Date:</b>	05/11/18	<b>Supersedes Date:</b>	04/25/17

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Heavy Duty 20 Spray Adhesive

#### Product Identification Numbers

62-4915-4920-0, 62-4915-4921-8, 62-4915-4925-9

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesive aerosol, Industrial Use

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Industrial Adhesives and Tapes Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Flammable Aerosol: Category 1.  
Gas Under Pressure: Liquefied gas.  
Serious Eye Damage/Irritation: Category 2B.  
Reproductive Toxicity: Category 2.  
Simple Asphyxiant.  
Specific Target Organ Toxicity (single exposure): Category 1.  
Specific Target Organ Toxicity (single exposure): Category 3.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

##### Signal word

Danger

**Symbols**

Flame | Gas cylinder | Exclamation mark | Health Hazard |

**Pictograms****Hazard Statements**

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child.

May displace oxygen and cause rapid suffocation.

Causes damage to organs:

cardiovascular system |

Causes damage to organs through prolonged or repeated exposure:

nervous system |

**Precautionary Statements****General:**

Keep out of reach of children.

**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see Notes to Physician on this label).

**Storage:**

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

Keep container tightly closed.

Store locked up in a well-ventilated place.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**Notes to Physician:**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

**Supplemental Information:**

Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Methyl acetate	79-20-9	25 - 35 Trade Secret *
Non-hazardous components (N.J.T.S. Reg No. 4499600-6761)	Trade Secret*	20 - 30 Trade Secret *
Dimethyl ether	115-10-6	15 - 25 Trade Secret *
Hexane	110-54-3	10 - 20 Trade Secret *
Isobutane	75-28-5	5 - 10 Trade Secret *
Propane	74-98-6	5 - 10 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. Get medical attention.

**Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional Comments</b>
Hexane	110-54-3	ACGIH	TWA:50 ppm	SKIN
Hexane	110-54-3	OSHA	TWA:1800 mg/m3(500 ppm)	
Dimethyl ether	115-10-6	AIHA	TWA:1880 mg/m3(1000 ppm)	

Propane	74-98-6	ACGIH	Limit value not established:	simple asphyxiant
Propane	74-98-6	OSHA	TWA:1800 mg/m3(1000 ppm)	
Isobutane	75-28-5	ACGIH	STEL:1000 ppm	
Methyl acetate	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	
Methyl acetate	79-20-9	OSHA	TWA:610 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists  
 AIHA : American Industrial Hygiene Association  
 CMRG : Chemical Manufacturer's Recommended Guidelines  
 OSHA : United States Department of Labor - Occupational Safety and Health Administration  
 TWA: Time-Weighted-Average  
 STEL: Short Term Exposure Limit  
 CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber  
 Nitrile Rubber

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator  
 Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Aerosol
<b>Odor, Color, Grade:</b>	Clear, Mild Solvent Odor
<b>Odor threshold</b>	No Data Available
<b>pH</b>	No Data Available
<b>Melting point</b>	No Data Available

<b>Boiling Point</b>	[Details:Aerosol]Not Applicable
<b>Flash Point</b>	-137 °F [Details:Propellant]
<b>Evaporation rate</b>	1.9 [Ref Std:ETHER=1]
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	No Data Available
<b>Flammable Limits(UEL)</b>	No Data Available
<b>Vapor Pressure</b>	No Data Available
<b>Vapor Density</b>	2.97 [Ref Std:AIR=1]
<b>Density</b>	0.75 g/ml
<b>Specific Gravity</b>	0.73 - 0.77 [Ref Std:WATER=1]
<b>Solubility in Water</b>	Nil
<b>Solubility- non-water</b>	No Data Available
<b>Partition coefficient: n-octanol/ water</b>	No Data Available
<b>Autoignition temperature</b>	No Data Available
<b>Decomposition temperature</b>	Not Applicable
<b>Viscosity</b>	Not Applicable
<b>Hazardous Air Pollutants</b>	<=16.8 % weight [Test Method:Calculated]
<b>Molecular weight</b>	No Data Available
<b>Volatile Organic Compounds</b>	<=378 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:Material VOC]
<b>Volatile Organic Compounds</b>	<=51.8 % [Test Method:calculated per CARB title 2]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

Intentional concentration and inhalation may be harmful or fatal.

Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

##### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

##### Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

##### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

#### Additional Health Effects:

##### Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause:

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

##### Prolonged or repeated exposure may cause target organ effects:

Peripheral Neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy.

##### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methyl acetate	Dermal	Rat	LD50 > 2,000 mg/kg

Methyl acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 49 mg/l
Methyl acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Hexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hexane	Inhalation-Vapor (4 hours)	Rat	LC50 170 mg/l
Hexane	Ingestion	Rat	LD50 > 28,700 mg/kg
Dimethyl ether	Inhalation-Gas (4 hours)	Rat	LC50 164,000 ppm
Isobutane	Inhalation-Gas (4 hours)	Rat	LC50 276,000 ppm
Propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
Non-hazardous components (N.J.T.S. Reg No. 4499600-6761)	Dermal	Not available	LD50 > 2,000 mg/kg
Non-hazardous components (N.J.T.S. Reg No. 4499600-6761)	Ingestion	Not available	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Methyl acetate	Rabbit	No significant irritation
Hexane	Human and animal	Mild irritant
Isobutane	Professional judgement	No significant irritation
Propane	Rabbit	Minimal irritation
Non-hazardous components (N.J.T.S. Reg No. 4499600-6761)	Professional judgement	No significant irritation

#### Serious Eye Damage/Irritation

Name	Species	Value
Methyl acetate	Rabbit	Moderate irritant
Hexane	Rabbit	Mild irritant
Isobutane	Professional judgement	No significant irritation
Propane	Rabbit	Mild irritant
Non-hazardous components (N.J.T.S. Reg No. 4499600-6761)	Professional judgement	No significant irritation

#### Skin Sensitization

Name	Species	Value
Methyl acetate	Human	Not classified
Hexane	Human	Not classified
Non-hazardous components (N.J.T.S. Reg No. 4499600-6761)		Not classified

#### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.



**Germ Cell Mutagenicity**

Name	Route	Value
Methyl acetate	In Vitro	Not mutagenic
Methyl acetate	In vivo	Not mutagenic
Hexane	In Vitro	Not mutagenic
Hexane	In vivo	Not mutagenic
Dimethyl ether	In Vitro	Not mutagenic
Dimethyl ether	In vivo	Not mutagenic
Isobutane	In Vitro	Not mutagenic
Propane	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Hexane	Dermal	Mouse	Not carcinogenic
Hexane	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Dimethyl ether	Inhalation	Rat	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Hexane	Ingestion	Not classified for development	Mouse	NOAEL 2,200 mg/kg/day	during organogenesis
Hexane	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during gestation
Hexane	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Inhalation	Toxic to male reproduction	Rat	LOAEL 3.52 mg/l	28 days
Dimethyl ether	Inhalation	Not classified for development	Rat	NOAEL 40,000 ppm	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Methyl acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Methyl acetate	Inhalation	blindness	Not classified		NOAEL Not available	
Methyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL Not available	8 hours
Hexane	Inhalation	respiratory system	Not classified	Rat	NOAEL 24.6 mg/l	8 hours
Dimethyl ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
Dimethyl ether	Inhalation	cardiac sensitization	Some positive data exist, but the	Dog	NOAEL	5 minutes

			data are not sufficient for classification		100,000 ppm	
Isobutane	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
Isobutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Isobutane	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	
Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
Methyl acetate	Inhalation	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
Hexane	Inhalation	peripheral nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 1.76 mg/l	13 weeks
Hexane	Inhalation	liver	Not classified	Rat	NOAEL Not available	6 months
Hexane	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.76 mg/l	6 months
Hexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 35.2 mg/l	13 weeks
Hexane	Inhalation	auditory system   immune system   eyes	Not classified	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	heart   skin   endocrine system	Not classified	Rat	NOAEL 1.76 mg/l	6 months
Hexane	Ingestion	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Ingestion	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL Not available	13 weeks
Dimethyl ether	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 25,000 ppm	2 years
Dimethyl ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks
Isobutane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks

**Aspiration Hazard**

Name	Value
Hexane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information

on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:**

**Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

Gas under pressure

**Health Hazards**

Reproductive toxicity

Serious eye damage or eye irritation

Simple Asphyxiant

Specific target organ toxicity (single or repeated exposure)

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

**Ingredient**  
Hexane

**C.A.S. No**  
110-54-3

**% by Wt**  
Trade Secret 10 - 20

Hexane (Hexane)

110-54-3

10 - 20

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 2 **Flammability:** 4 **Instability:** 0 **Special Hazards:** None  
**Aerosol Storage Code:** 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	26-9520-3	<b>Version Number:</b>	6.01
<b>Issue Date:</b>	05/11/18	<b>Supersedes Date:</b>	04/25/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)