



BRICKFORM® Triple Seven Bond-Coat™

Reactive Primer

FEATURES:

- “Reactive Primer”
- Easy application
- Greatly enhances bonding to concrete
- Prevents the sub floor from absorbing moisture from overlay
- Interior or exterior use
- Great for priming all masonry surfaces: concrete, tile, terrazzo, brick, and overlays.
- Overlay may be applied on bond coat whether it’s wet or dry for up to two hours.

PRODUCT DESCRIPTION

BRICKFORM Triple Seven Bond Coat is a high-strength, premium, water-based, copolymer that provides added bond-strength, and is the perfect primer for BRICKFORM Stampable Overlay, Micro-Topping and SM Professional Grade. Because BRICKFORM Triple Seven Bond Coat re-emulsifies when wet, it is preferred over other acrylic primers for concrete resurfacing products. BRICKFORM Triple Seven Bond Coat can be used on any concrete surface.

SURFACE PREPARATION

Surface must be clean and free of contaminants, old polishes must be removed, and the floor must be completely dry before application. New concrete should be cured for at least 14 days. The floor should be adequately profiled via mechanical or chemical means to ensure proper bonding.

APPLICATION

BRICKFORM strongly recommends representative jobsite test sections. The surface of the concrete must be scarified or sandblasted and be completely free from all dirt, oil, paint, moss, dust, and other contaminants. After scarifying or sandblasting, power-wash the concrete surface. Remove any standing water, and allow the surface to partially dry before applying BRICKFORM Triple Seven Bond Coat.

To ensure bond-strength, BRICKFORM Triple Seven Bond Coat must be used on the concrete surface prior to applying BRICKFORM Stampable Overlay, Micro-Topping or SM Professional Grade. Apply full-strength, directly onto the concrete surface. Can be brushed on or rolled on using a short-napped roller. BRICKFORM Triple Seven Bond Coat can also be applied using a low-pressure, airless sprayer. Apply a thin coat; if surface is very porous, a second coat may be necessary. Overlay can be applied immediately after primer placement, no lengthy drying time needed. The primer remains reactive for two hours, if two or more hours elapse, re-spray primer over affected area and then place overlay.

STORAGE

Product should NOT be stored in temperatures above 90°F. Keep containers tightly sealed DO NOT allow product to freeze. DO NOT store for more than one year.

COVERAGE

One gallon of Triple Seven BOND COAT should cover 160 to 200 square feet per gallon (800 to 1200 square feet per 5 gallon bucket). Coverage will vary according to the porosity and composition of the floor material.

TRIPLE SEVEN BOND COAT PROPERTIES

Coverage	160-200 square feet/gallon
Drying time.....	30 - 60 minutes
Leveling	Excellent
pH	8.0 - 9.0
Recoat	Very good
Shelf life	1 year
Specific gravity.....	1.04

WARRANTY

This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or as results of such use. In any case, the manufacturer’s obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product’s suitability and assume all risks and liability.

MANUFACTURER

BRICKFORM, A Division of Solomon Colors, Inc.

ORDER SPECIFICATIONS

Triple Seven Bond Coat

Shipping Weight	Container Size	Item No.
40 lbs (18.9 L)	5 gallon	BC-007
10 Lbs (4.5 kg)	1 gallon	BC-0071