



SUPER CLEAR COAT MATTE

Cure, seal, and color enhance exposed aggregate or concrete

April 2019 Version 1.3

1. PRODUCT NAME

Super Clear Coat Matte

2. MANUFACTURER

Super Clear Coat Matte is manufactured for Cemstone Products Company
2025 Centre Pointe Blvd., Suite 300
Mendota Heights, MN 55120 USA

Phone: 1-800-CEMSTONE

Local: 651-688-9292

Internet: cemstone.com

3. PRODUCT DESCRIPTION

Super Clear Coat Matte is used for curing and sealing exposed aggregate and sealing colored concrete. Made with a blend of methacrylate polymers. This aromatic solvent-based coating does not yellow when exposed to the sun's UV rays

WHEN/WHERE TO USE

- Above-grade exterior applications
- Vertical or horizontal applications
- New or existing applications
- Final seal for colored concrete, terrazzo, natural and synthetic stone, paving stone, brick, stucco, quarry tile, burnish block, or other cementitious materials
- Also aids in curing new exposed aggregate & non-colored concrete

ADVANTAGES

- Color enhancing, darkens the color and adds matte finish
- Non-staining, non-yellowing
- Ready to use, do not dilute
- Minimizes spalling and aggregate pops by penetrating into the surface of the concrete or exposed aggregate to fill gaps and voids
- Makes surfaces less dusty and easier to clean, including grease or rust stains on garage floors and driveways
- Can be applied to new non-colored concrete as a curing compound, to reduce the loss of water during the hardening process
- Easy to apply with sprayer, roller, or long nap applicator
- Forms a membrane to increase protection from damaging freeze-thaw cycles, deicing salts, efflorescence, and chemical erosion
- Protects from most chemicals, airborne pollutants dirt, foods, acids, alkali, oil, grease, for easier to clean surfaces.
- Protects from effects of rain water penetration, chemicals, oils, salt, freeze-thaw, smog, and contaminants

- 2-hour drying time to be open to traffic under normal conditions
- Wear patterns can be easily re-coated

Warning

Avoid contact with eyes and skin. If contact with eyes occurs, flood eyes repeatedly with clean water for 15 minutes and see a physician immediately. Do not rub eyes. Wash hands thoroughly after handling or before eating with warm, soapy water. Do not take internally. KEEP OUT OF REACH OF CHILDREN.

4. TECHNICAL DATA

TECHNICAL DATA	
Composition and Materials	A blend of 100% methacrylate acrylic polymers in a fast-drying aromatic solvent. No fillers are used and there are no oils or saponifiable resins. Cemstone products are manufactured with only the finest quality raw materials available and close quality-control is practiced.
Percent Solids	25%
Flash Point	105°F (40.5°C)
Typical Drying Time @ 70°F	1 hour (touch) 2 hours (traffic)
VOC Content	< 700 g/l
A.I.M. Category	Curing and Sealing Compound Maximum VOC 700 g/l
Applicable Standards	ASTM C-309, Type 1, Class A, B and Type 1D with a red dye added. Fed. TT-C-800A, Type 1, Class 1 AASHTO Des. M-148, Type 1, Clear DE CRD— C300 USDA Authorization for use in meat, poultry, and food processing plants. Resilient Tile Institute approval for compatibility with most resilient tile, carpet adhesives, and paints

5. INSTALLATION PREPARATION

Read all directions before starting work. Apply only to dry surfaces for optimal performance. Do not apply when rain is expected within 4-6 hours of application. Super Clear Coat Matte will not freeze, however it must be allowed to warm to 50°F (10°C) prior to using. Contains aromatic hydrocarbon. DO NOT STORE OR USE

NEAR HEAT OR OPEN FLAME. Keep containers tightly sealed when not in use, and use only in well-ventilated areas. Read and understand Safety Data Sheet pages available from Cemstone Products for all safety precautions prior to use.

NOTE: A prime coat of Cure & Seal or Super Clear Coat is necessary to satisfy porosity prior to application of Super Clear Coat Matte.

New Concrete: Allow surface water to completely dissipate.

Colored Concrete: Do not use as a curing agent on freshly poured colored concrete. Color will be intensified with Super Clear Coat Matte. Apply only when the colored concrete has fully cured, is dry, and the color looks uniform.

Existing Concrete: Repair any cracks or damaged areas. Surfaces must be clean, dry, and free from oil, grease, dust, and curing compounds (especially wax based). Surface must be dry to not trap moisture between the film and the concrete slab, which can cause a white film to develop.

Paving Block, Patio Stone, Brick and Exposed Aggregate: Surfaces must be clean and dry to avoid trapping moisture.

Stamped Concrete: Proper washing is important, any abundance of oil from a liquid release agent can block adhesion of the Super Clear Coat Matte. When using a powdered release agent, delaminating of the sealer may occur if the proper amount of release is not washed off the surface prior to sealer application.

MIXING

- Mixture should be gently stirred to suspend matting agent prior to use. Do not entrain air.
- Do not dilute with water or solvents.

APPLICATION

- Apply when both air and surfaces temperatures are above 40°F (4.4°C) and the Super Clear Coat Matte is above 50°F (10°C). For best results, avoid application in direct sunlight.
- Gently stir to suspend matting agent but do not entrain air.
- Apply uniformly at the specified rate of coverage with long-nap roller or an airless sprayer equipped with PVC, viton, or other compatible fittings and hoses as solvents can damage rubber.
- Work the Super Clear Coat Matte into the concrete, avoiding pools, runs, or sags.



SUPER CLEAR COAT MATTE

Cure, seal, and color enhance exposed aggregate or concrete

April 2019 Version 1.3

- Surface should have a uniform coating
- Allow first coating to thoroughly dry prior to application of a second coating.

Exposed Aggregate: Exposed aggregate requires application in two coats: the first thin coat of Super Clear Coat is used to cure and satisfy porosity. The second thin coat is used to matte the gloss and forms a clear film to enhance coloring and protect surfaces. When using as a curing compound, the surface should first be washed with a mild acid solution to remove the thin film of cement dust, then thoroughly rinsed and allowed to dry prior to application of a thin coating of Super Clear Coat Matte. The final coat is applied once the exposed aggregate has fully cured.

NOTE: Super Clear Coat Matte will darken the appearance of concrete, especially if it is applied too heavily. A small mock-up in an inconspicuous area is often done to test compatibility with the substrate prior to full application. When applying to existing areas surfaces must be clean and dry.

CLEAN UP

Use mineral spirits or solvent-based cleaners, such as xylene on tools and equipment. For sprayers, pump the solvent through the spray equipment to remove any residue to prevent clogs in the hose and wand. For skin contact, wash thoroughly with soap and warm water.

Approximate Coverage @ 70°F (21°C)	Sq. Ft./ gal.	M ² / L
Curing exposed aggregate	300-500	7.3-12.3
Second coat, cured concrete, burnished block	300-500	7.3-12.3

COVERAGE

NOTE: Coverage is per coating and may vary due to porosity, wind, temperatures, and condition of surfaces.

NOTES

- Super Clear Coat Matte is not recommended as a curing agent on freshly-poured colored concrete, as a sealer on asphalt, surfaces subject to hydrostatic pressure, or as a water-proofing agent for below-grade.
- Existing surfaces must be fully dry to not trap moisture between the film and

the concrete slab, which can cause a white film to develop.

- Since it is a solvent-based sealer, keep away from heat and flame. Use only with sufficient ventilation, do not breathe vapor or mist, wear the appropriate properly fitted NIOSH/MSHA approved respirator. Close container tightly after each use.
- Concrete mixes containing calcium chloride will remain dark longer when sealed. Be aware of possible extenders and additives to your concrete which can create inconsistent porosity and coverage ratios. Please check with your concrete supplier to see if additives or extenders will need to be adjusted to compensate for these variations.
- Popout or scaling issues can occur with any concrete installation, but are more likely in extreme hot weather conditions (above 90°F), and when finished by heavy steel troweling. In certain regional areas a reaction between the silica in the shale particles and the sodium and potassium alkali in the Portland cement can increase the occurrence. It is not recommended Super Clear Coat Matte be used as a curing compound when these conditions exist, however a seal coat can be applied for protection and dust-proofing when the concrete is fully cured and dry.
- Some fumes may be present during application. Use best practices when applying on interiors for proper ventilation. Super Clear Coat Matte is non-toxic in its cured state.
- Dispose of contents/container in accordance with all local and state regulations.
- Do not dilute with water or solvents.
- For best use, the recommended shelf life is 12 months. If shelf life is beyond 12 months, please contact your distributor.

6. AVAILABLE SIZES

- 1 gal. (3.78 L) can
- 5 gal. (18.9 L) pail
- 55 gal. (208 L) drum

7. WARRANTY

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, expressed or implied, including, but not limited to those concerning merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that Seller's liability to the Buyer shall not exceed the total amount billed and billable to the Buyer for the product hereunder.

8. MAINTENANCE

Normal sweeping, dusting, or mopping. If spillage removes the coating, or if traffic wear patterns occur Super Clear Coat Matte can be re-applied to the affected area.

9. TECHNICAL SERVICES

The Cemstone office offers assistance with specifications, performance test data and field services.

10. FILING SYSTEM

Division 9

CEMSTONE DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question to the suitability of a particular product, a small test patch is recommended. See also WARRANTY (Section 7).

KEEP AWAY FROM HEAT OR OPEN FLAME

WARNING: INJURIOUS TO EYES

KEEP OUT OF REACH OF CHILDREN

FOR PROFESSIONAL USE ONLY