

# SAFETY DATA SHEET

Issue Date 02-Nov-2018

CS-500

Revision Date 12-Aug-2019

Version 3

Blush-Tone Acid Stain Mahogany

# **1. IDENTIFICATION**

<u>Product identifier</u> Product Name	Blush-Tone Acid Stain Mahogany
Other means of identification Product Code	CS-500
Recommended use of the chemical	
Recommended Use	Restricted to professional users.
Uses advised against	Consumer use
Details of the supplier of the safety Supplier Address Solomon Colors, Inc. 4050 Color Plant Road Springfield, IL 62702	<u>data sheet</u> <u>Manufacturer Address</u> Solomon Colors, Inc. 4050 Color Plant Road Springfield, IL 62702
Company Phone Number 24 Hour Emergency Phone Number	800-624-0261 (US & Canada); 217-522-3112 (Outside North America) 800-373-7542 Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemical
	2. HAZARDS IDENTIFICATION

#### **Classification**

## **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4.
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 1
Subcategory	Sub-category A
Serious eye damage/eye irritation	Category 1
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1B
Specific target organ toxicity (repeated	Category 1
exposure)	

# Label elements

Emergency Overview

# Danger

#### Hazard statements

Harmful if swallowed Harmful if inhaled Causes severe skin burns and eye damage May cause allergy or asthma symptoms or breathing difficulties if inhaled May cause an allergic skin reaction May cause genetic defects May cause cancer May damage fertility or the unborn child Causes damage to organs through prolonged or repeated exposure

Appearance aqueous solution

Physical state Liquid

Odor Strong Pungent

# **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Do not breathe dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area In case of inadequate ventilation wear respiratory protection Contaminated work clothing must not be allowed out of the workplace

#### **Precautionary Statements - Response**

Immediately call a POISON CENTER or doctor Specific treatment (see supplemental information on this label) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower Wash contaminated clothing before reuse If skin irritation or rash occurs: Get medical advice/attention IF INHALED: Remove person to fresh air and keep comfortable for breathing Immediately call a POISON CENTER or doctor IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell Rinse mouth Do NOT induce vomiting

# **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

#### Other Information

• Very toxic to aquatic life with long lasting effects

· Very toxic to aquatic life

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No.	Weight-%	Trade Secret
Ferrous Chloride	7758-94-3	5 - 15	*

Manganese Chloride	7773-01-5	5 -10	*
Hydrochloric acid	7647-01-0	< 10	*
Sodium dichromate	10588-01-9	< 5	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### **Description of first aid measures**

General advice	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).	
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
Skin Contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	
Inhalation	Move to fresh air in case of accidental inhalation of vapors or decomposition products. Call a physician or poison control center immediately.	
Ingestion	If swallowed, call a poison control center or physician immediately. Clean mouth with water and drink afterwards plenty of water.	
Most important symptoms and effe	Most important symptoms and effects, both acute and delayed	
Symptoms	May be harmful if swallowed or if inhaled. Causes severe skin burns and eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. May cause genetic defects. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Treat symptomatically.	
5. FIRE-FIGHTING MEASURES		

# Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

Contact with metals may evolve flammable hydrogen gas. Non-combustible, substance itself does not burn but may decompose upon heating to produce corrosive and/or toxic fumes. Runoff may pollute waterways.

Hazardous combustion products Thermal decomposition can lead to the release of irritating gases and vapors. Carbon oxides. Chromium oxides. Hydrogen chloride.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

# Personal precautions, protective equipment and emergency procedures

Personal precautions	Keep people away from and upwind of spill/leak. Ventilate affected area. Avoid contact with skin, eyes and inhalation of vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Stop leak if you can do it without risk.
Environmental precautions	
Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional ecological information.
Methods and material for containm	ent and cleaning up
Methods for containment	Dike far ahead of liquid spill for later disposal. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).
Methods for cleaning up	Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
	7. HANDLING AND STORAGE
Precautions for safe handling	
Advice on safe handling	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling.
Conditions for safe storage, includ	ing any incompatibilities
Storage Conditions	Keep container tightly closed in a dry and well-ventilated place. Keep/store only in original container. Keep in properly labeled containers. Keep from freezing.
Incompatible materials	Strong oxidizing agents. Metals. Alkali.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ferrous Chloride 7758-94-3	TWA: 1 mg/m³ Fe	(vacated) TWA: 1 mg/m <sup>3</sup> Fe	TWA: 1 mg/m <sup>3</sup> Fe
Manganese Chloride 7773-01-5	TWA: 0.02 mg/m <sup>3</sup> Mn respirable particulate matter TWA: 0.1 mg/m <sup>3</sup> Mn inhalable particulate matter	(vacated) Ceiling: 5 mg/m³ Ceiling: 5 mg/m³ Mn	IDLH: 500 mg/m <sup>3</sup> Mn TWA: 1 mg/m <sup>3</sup> Mn STEL: 3 mg/m <sup>3</sup> Mn
Hydrochloric acid 7647-01-0	Ceiling: 2 ppm	(vacated) Ceiling: 5 ppm (vacated) Ceiling: 7 mg/m <sup>3</sup> Ceiling: 5 ppm Ceiling: 7 mg/m <sup>3</sup>	IDLH: 50 ppm Ceiling: 5 ppm Ceiling: 7 mg/m <sup>3</sup>
Sodium dichromate 10588-01-9	STEL: 0.0005 mg/m <sup>3</sup> Cr(VI) inhalable particulate matter TWA: 0.0002 mg/m <sup>3</sup> Cr(VI) inhalable particulate matter S*	TWA: 5 μg/m <sup>3</sup> (vacated) Ceiling: 0.1 mg/m <sup>3</sup> Ceiling: 0.1 mg/m <sup>3</sup> CrO3 applies to any operations or sectors for which the Hexavalent Chromium standard [29 CFR 1910.1026] is stayed or is otherwise not in effect	IDLH: 15 mg/m <sup>3</sup> Cr(VI) TWA: 0.0002 mg/m <sup>3</sup> Cr

NIOSH IDLH Immediately Dangerous to Life or Health

Other InformationVacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d<br/>962 (11th Cir., 1992).

#### Appropriate engineering controls

Engineering Controls	Ensure adequate ventilation, especially in confined areas. Showers
	Eyewash stations
	Ventilation systems.

#### Individual protection measures, such as personal protective equipment

Eye/face protection	Tight sealing safety goggles. Face protection shield.
Skin and body protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	Wash face, hands and any exposed skin thoroughly after handling. Use personal protective equipment as required. Avoid prolonged or repeated contact with skin. Avoid breathing (dust, vapor, mist, gas). Wash contaminated clothing before reuse.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Appearance Color	Liquid aqueous solution Mahogany	Odor Odor threshold
<u>Property</u> pH Melting point/freezing point Boiling point / boiling range Flash point Evaporation rate	<u>Values</u> No information available No information available No information available No information available No information available	<u>Remarks • Method</u>

Strong Pungent

No information available

Flammability (solid, gas) Flammability Limit in Air	No information available
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	No information available
Water solubility	No information available
Solubility in other solvents	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available
Other Information	
Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	No information available
Bulk density	No information available

# **10. STABILITY AND REACTIVITY**

#### **Reactivity**

No data available

#### Chemical stability

Stable under normal conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

#### Hazardous polymerization

Hazardous polymerization does not occur.

## Conditions to avoid

Strong oxidizing agents. Storage near to reactive materials. To avoid thermal decomposition, do not overheat.

#### Incompatible materials

Strong oxidizing agents. Metals. Alkali.

#### **Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Carbon oxides. Chromium oxides. Hydrogen chloride.

# 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Product Information	May be harmful if swallowed or if inhaled. Causes severe skin burns and eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. May cause genetic defects. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.
Inhalation	Harmful by inhalation. Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. May cause sensitization by inhalation.
Eye contact	Corrosive to the eyes and may cause severe damage including blindness.
Skin Contact	Corrosive. Contact causes severe skin irritation and possible burns. The product causes burns of eyes, skin and mucous membranes. May cause an allergic skin reaction.
Ingestion	Harmful if swallowed. Ingestion causes burns of the upper digestive and respiratory tracts.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ferrous Chloride 7758-94-3	= 450 mg/kg (Rat)	-	-
Manganese Chloride 7773-01-5	= 250 mg/kg (Rat)	-	-
Hydrochloric acid 7647-01-0	238 - 277 mg/kg (Rat)	> 5010 mg/kg (Rabbit)	= 1.68 mg/L (Rat)1 h
Sodium dichromate 10588-01-9	= 46 mg/kg (Rat)	= 960 mg/kg (Rabbit)	= 200 mg/m³(Rat)4 h

#### Information on toxicological effects

#### Symptoms

Acute Toxicity - Oral- Cat. 4: Harmful if swallowed. Acute Toxicity-Inhalation -Cat 4. Harmful if inhaled. (based on ATE for mixture components).

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure\_

Skin corrosion/irritation Serious eye damage/eye irritation	Skin Corrosion Cat 1. (based on mixture components). Causes severe burns. <b>n</b> Eye Damage Cat 1. (based on mixture components). Risk of serious damage to eyes.	
Sensitization	Respiratory Sensitizer Cat. 1. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin Sensitizer Cat 1. May cause an allergic skin reaction.	
Germ cell mutagenicity	Mutagenic. Contains a known or suspected mutagen.	

Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.			
Chemical Name	ACGIH	IARC	NTP	OSHA
Hydrochloric acid 7647-01-0	-	Group 3	-	-
Sodium dichromate 10588-01-9	A1	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity STOT - single exposure STOT - repeated exposure Product is or contains a chemical which is a known or suspected reproductive hazard. Not classified. (Based on mixture components).

**F - repeated exposure** STOT RE 1 - Central Nervous System. Liver.

Chronic toxicityRepeated or prolonged exposure may cause central nervous system damage. May cause<br/>adverse liver effects.Aspiration hazardNot classified. (Based on mixture components).

#### Numerical measures of toxicity - Product Information

A1 - Known Human Carcinogen

IARC (International Agency for Research on Cancer)

NTP (National Toxicology Program)

Known - Known Carcinogen

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	803.4 mg/kg
ATEmix (dermal)	6564 mg/kg
ATEmix (inhalation-gas)	29496 mg/l
ATEmix (inhalation-dust/mist)	1.01 mg/l

# **12. ECOLOGICAL INFORMATION**

This product contains a chemical which, although not listed, meets the IMDG criteria for being a severe marine pollutant.

#### **Ecotoxicity**

This product has not been fully evaluated on the product level. This product contains substances that are known to be toxic to aquatic life with long lasting effects.

#### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

No information available

#### **13. DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

**Disposal of wastes** Should not be released into the environment. Rinse water resulting from cleanup should be collected for treatment before disposal. Solutions with low pH-value should be neutralized. Disposal should be in accordance with applicable regional, national and local laws and regulations.

#### Contaminated packaging

Do not reuse container.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Manganese Chloride	Toxic
7773-01-5	
Sodium dichromate	Toxic
10588-01-9	Corrosive
	Ignitable

# **14. TRANSPORT INFORMATION**

DOT UN/ID no. Proper shipping name Hazard Class Packing Group Marine pollutant	Not regulated for ground shipment in inner packaging not over 5.0 L (1.3 gallons) net capacity each for liquids, packed in a strong outer packaging. (See D.O.T 49 CFR 173.154(b)(2) under Exemptions for Class 8) UN3264 Corrosive Liquid, Acidic, Inorganic, n.o.s. (Hydrochloric Acid) 8 III This product contains a chemical which, although not listed, meets the IMDG criteria for being a severe marine pollutant.
<u>TDG</u> UN/ID no. Proper shipping name Hazard Class Packing Group Marine pollutant	UN3264 Corrosive Liquid, Acidic, Inorganic, n.o.s. (Hydrochloric Acid) 8 III This product contains a chemical which is listed as a marine pollutant according to TDG.
<u>MEX</u> UN/ID no. Proper shipping name Hazard Class Packing Group	UN3264 Corrosive Liquid, Acidic, Inorganic, n.o.s. (Hydrochloric Acid) 8 III
<u>ICAO (air)</u> UN/ID no. Proper shipping name Hazard Class Packing Group	UN3264 Corrosive Liquid, Acidic, Inorganic, n.o.s. (Hydrochloric Acid) 8 III
<u>IATA</u> UN/ID no. Proper shipping name Hazard Class Packing Group	UN3264 Corrosive Liquid, Acidic, Inorganic, n.o.s. (Hydrochloric Acid) 8 III
IMDG UN/ID no. Proper shipping name Hazard Class Packing Group Marine pollutant	UN3264 Corrosive Liquid, Acidic, Inorganic, n.o.s. (Hydrochloric Acid) 8 III This material meets the definition of a marine pollutant

# **15. REGULATORY INFORMATION**

#### International Inventories TSCA DSL/NDSL EINECS/ELINCS ENCS

Complies
Complies

#### Legend:

IECSC

KECL

PICCS

AICS

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

Complies

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### US Federal Regulations

## SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
Hydrochloric acid - 7647-01-0	1.0	
Sodium dichromate - 10588-01-9	0.1	
Manganese Chloride - 7773-01-5	1.0	

# SARA 311/312 Hazard Categories

See section 2 for more information

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ferrous Chloride 7758-94-3	100 lb	-	-	Х
Hydrochloric acid 7647-01-0	5000 lb	-	-	Х
Sodium dichromate 10588-01-9	10 lb	Х	-	Х

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ferrous Chloride	100 lb	-	RQ 100 lb final RQ
7758-94-3			RQ 45.4 kg final RQ
Hydrochloric acid	5000 lb	5000 lb	RQ 5000 lb final RQ
7647-01-0			RQ 2270 kg final RQ
Sodium dichromate	10 lb	_	RQ 10 lb final RQ
10588-01-9			RQ 4.54 kg final RQ

#### US State Regulations

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
Hexavalent chromium - 18540-29-9	Carcinogen	

Developmental	
Female Reproductive	
Male Reproductive	

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Ferrous Chloride 7758-94-3	Х	X	Х
Hydrochloric acid 7647-01-0	Х	X	Х
Sodium dichromate 10588-01-9	Х	X	Х
Manganese Chloride 7773-01-5	Х	-	Х

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 3	Flammability 1	Reactivity 0	Physical and Chemical Properties -
HMIS_	Health hazards 3	Flammability 1	Physical hazards 0	Personal protection X

Prepared By Issue Date Revision Date Revision Note Periodic Review Solomon Colors - Lab Technical Services 02-Nov-2018 12-Aug-2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### End of Safety Data Sheet