



# SAFETY DATA SHEET

## SECTION 1) IDENTIFICATION

**Product ID:** Cemstone Cure & Seal  
**Product Name:** Concrete Curing Compound  
**Revision Date:** Feb 15, 2024 **Date Printed:** Apr 23, 2024  
**Version:** 2.0 **Supersedes Date:** Feb 15, 2024  
**Manufacturer's Name:** Cemstone Products Company  
**Address:** 2025 Centre Pointe Blvd Mendota Heights, MN, US, 55120  
**Emergency Phone:** 800-424-9300  
**Information Phone Number:** 651-688-9292  
**Fax:**  
**Product/Recommended Uses:**

## SECTION 2) HAZARDS IDENTIFICATION

### Classification

Flammable Liquids - Category 3  
Aspiration Hazard - Category 1  
Carcinogenicity - Category 2  
Eye Irritation - Category 2B  
Germ Cell Mutagenicity - Category 1B  
Skin Irritation - Category 2  
Skin Sensitizer - Category 1  
Specific Target Organ Toxicity - Repeated Exposure - Category 2  
Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) - Category 3  
Acute aquatic toxicity - Category 3  
Chronic aquatic toxicity - Category 3

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

### Pictograms



### Signal Word

Danger

### Hazardous Statements - Health

H304 - May be fatal if swallowed and enters airways  
H351 - Suspected of causing cancer  
H320 - Causes eye irritation

- H340 - May cause genetic defects
- H315 - Causes skin irritation
- H317 - May cause an allergic skin reaction
- H373 - May cause damage to organs through prolonged or repeated exposure
- H335 - May cause respiratory irritation

#### **Hazardous Statements - Physical**

- H226 - Flammable liquid and vapor

#### **Hazardous Statements - Environmental**

- H412 - Harmful to aquatic life with long lasting effects

#### **Precautionary Statements - General**

- P101 - If medical advice is needed, have product container or label at hand.
- P102 - Keep out of reach of children.
- P103 - Read label before use.

#### **Precautionary Statements - Prevention**

- P273 - Avoid release to the environment.
- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P280 - Wear protective gloves, protective clothing, eye protection/face protection.
- P264 - Wash thoroughly after handling.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 - Keep container tightly closed.
- P240 - Ground/bond container and receiving equipment.
- P241 - Use explosion-proof electrical/ventilating/lighting equipment.
- P242 - Use only non-sparking tools.
- P243 - Take action to prevent static discharges.
- P272 - Contaminated work clothing should not be allowed out of the workplace.
- P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
- P271 - Use only outdoors or in a well-ventilated area.

#### **Precautionary Statements - Response**

- P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
- P331 - Do NOT induce vomiting.
- P308 + P313 - IF exposed or concerned: Get medical advice/attention.
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 - If eye irritation persists: Get medical advice/attention.
- P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P370 + P378 - In case of fire: Use carbon-di oxide, alcohol foam, water spray or dry chemical to extinguish.
- P302 + P352 - IF ON SKIN: Wash with plenty of water.
- P321 - Specific treatment (see First-Aid on this label).
- P362 + P364 - Take off contaminated clothing. And wash it before reuse.
- P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.
- P314 - Get Medical advice/attention if you feel unwell.
- P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 - Call a POISON CENTER/doctor if you feel unwell.

#### **Precautionary Statements - Storage**

P405 - Store locked up.

P403 + P235 - Store in a well-ventilated place. Keep cool.

P403 + P405 - Store in a well-ventilated place. Store locked up.

### Precautionary Statements - Disposal

P501 - Dispose of contents/container in accordance with local/national/international regulations.

### Hazards Not Otherwise Classified (HNOC)

None.

Acute toxicity of less than one percent of the mixture is unknown

## SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	GHS Classifications	% By Weight
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	Acute Tox. Oral 5, H303; Asp. Tox. 1, H304; Carc. 2, H351; Flam. Liq. 3, H226; Muta. 1B, H340; Skin Irr. 2, H315	30% - 60%
0064742-88-7	MEDIUM MINERAL SPIRITS	Asp. Tox. 1, H304; Carc. 2, H351; Eye Irr. 2B, H320; Flam. Liq. 3, H226; STOT RE 2, H373; STOT SE 3 (Narc.), H336	30% - 60%
0026636-08-8	2-PROPENOIC ACID, 2-METHYL-, POLYMER WITH ETHENYLBENZENE AND 2-ETHYLHEXYL 2-PROPENOATE	N.A.	15% - 40%
0000095-63-6	1,2,4-TRIMETHYLBENZENE	Acute Tox. Inh. 4, H332; Acute Tox. Oral 5, H303	1% - 5%
0000108-67-8	MESITYLENE	Acute Tox. Oral 5, H303	0% - 1%
0000526-73-8	1,2,3-TRIMETHYLBENZENE	N.A.	0% - 1%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

## SECTION 4) FIRST-AID MEASURES

### Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Get Medical advice/attention if you feel unwell. Eliminate all ignition sources if safe to do so. If exposed/If you feel unwell/If concerned: Call a POISON CENTER/doctor. Take precautions to ensure your own safety (e.g. wear appropriate protective equipment).

### Eye Contact

If eye irritation persists: Get medical advice/attention. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. Avoid direct contact. Wear chemical protective gloves, if necessary.

### Skin Contact

IF exposed or concerned: Get medical advice/attention. Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. Store contaminated clothing under water and wash before re-use or discard. If skin irritation or a rash occurs: Get medical advice/attention. Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts).

### Ingestion

Rinse mouth. Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.

### Most important symptoms and effects, both acute and delayed

No data available.

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. No specific treatment is required. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Treat according to symptoms (decontamination, vital functions), no known specific antidote. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

## SECTION 5) FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Small Fire : Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Large Fire : Water spray, fog or alcohol-resistant foam.

### Unsuitable Extinguishing Media

Do not use straight stream of water.

### Specific Hazards Arising from the Chemical

Fire will produce irritating gases. Runoff may pollute waterways. Most vapors are heavier than air. Vapors may form explosive mixtures with air. Vapors will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Many liquids are lighter than water. Containers may explode in fire. May form an ignitable vapor/air mixture in closed tanks or containers.

### Precautions for Firefighters

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

### Special Protective Equipment

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## SECTION 6) ACCIDENTAL RELEASE MEASURES

### Emergency Procedure

Stay uphill and/or upstream. Ventilate closed spaces before entering. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing. Evacuate and isolate hazard area and keep unauthorized personnel away. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. A vapor-suppressing foam may be used to reduce vapors.

### Protective Equipment

Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA).

### Personal Precautions

Do not breathe vapor or mist. Do not get on skin, eyes or clothing.

### Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Dike far ahead of liquid spill for later disposal.

### Methods and Materials for Containment and Cleaning up

Ventilate area after clean-up is complete. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean, non-sparking tools to collect absorbed material.

## SECTION 7) HANDLING AND STORAGE

### General

Wash hands after use. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. All containers must be properly labelled. Do not get in eyes, on skin, or on clothing. Eyewash stations and showers should be available in areas where this material is used and stored. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not breathe vapor or mist.

### Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

### Storage Room Requirements

Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Indoor storage should meet OSHA standards and appropriate fire codes. Empty containers retain residue and may be dangerous. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and strong oxidizers. Store in approved containers and protect against physical damage. Take precautionary measures against electrostatic discharge. To avoid fire or explosion, dissipate static electricity.

## SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

### Eye protection

Wear eye protection with side shields or goggles.

Wear indirect-vent, impact and splash resistant goggles when working with liquids.

### Skin Protection

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Use of chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and microorganisms. Examples of preferred glove barrier materials include: Butyl rubber, Polyethylene, Chlorinated polyethylene, Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Viton, Neoprene, Polyvinyl chloride ("PVC" or "vinyl"), Nitrile/butadiene rubber ("nitrile" or "NBR").

Full contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M).

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 30 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M).

Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.

It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers.

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves.

Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity.

Always seek advice from glove suppliers.

Contaminated gloves should be replaced.

Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber.

Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

### Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

### Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	OSHA TWA (mg/m3)
1,2,3-TRIMETHYLBENZENE		10				CNS impair; hematologic eff		
1,2,4-TRIMETHYLBENZENE		10			A4	CNS impair; hematologic eff		
AROMATIC HYDROCARBON MIXTURE >C9	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];	(L)[N159](L)[N800]			[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr [N159]URT irr [N800]	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	2000
MEDIUM MINERAL SPIRITS	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];	(L)[N159](L)[N800]			[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr [N159]URT irr [N800]	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	
MESITYLENE		10				CNS impair; hematologic eff		

Chemical Name	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (Z1, Z2, Z3)	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)
1,2,3-TRIMETHYLBENZENE							125	25
1,2,4-TRIMETHYLBENZENE							125	25
AROMATIC HYDROCARBON MIXTURE >C9	500					1		
MEDIUM MINERAL SPIRITS								
Mesitylene							125	25

Chemical Name	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen
1,2,3-TRIMETHYLBENZENE			
1,2,4-TRIMETHYLBENZENE			
AROMATIC HYDROCARBON MIXTURE >C9			
MEDIUM MINERAL SPIRITS			
Mesitylene			

A4 - Not Classifiable as a Human Carcinogen, CNS - Central nervous system, eff - Effects, impair - Impairment, URT - Upper respiratory tract

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	7.60 lb/gal
Specific Gravity	0.91
% Solids By Weight	25.00%
Appearance	N/A
Odor Description	N/A
pH	N/A
Water Solubility	Insoluble in water
Flammability	Flash point at or above 100°F/38°C and less than 200°F/93°C
Flash Point	107.00 °F
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A

Low Boiling Point	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A

## SECTION 10) STABILITY AND REACTIVITY

### Reactivity

No data available.

### Chemical Stability

Stable under normal storage and handling conditions.

### Possibility of Hazardous Reactions/Polymerization

Will not occur.

### Conditions To Avoid

Avoid all possible sources of ignition, heat, sparks, flame, build up of static electricity and contact with incompatible materials.

### Incompatible Materials

Strong bases, acids, and oxidizing agents.

### Hazardous Decomposition Products

Oxides of carbon.

## SECTION 11) TOXICOLOGICAL INFORMATION

### Acute Toxicity

Based on available data, the classification criteria are not met.

The Acute Toxicity Estimate (ATE) for an oral exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for a dermal exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for an inhalation (vapour) exposure to this mixture is >20 mg/l

### Aspiration Hazard

May be fatal if swallowed and enters airways

### Carcinogenicity

Suspected of causing cancer

### Germ Cell Mutagenicity

May cause genetic defects

### Reproductive Toxicity

Based on available data, the classification criteria are not met.

### Respiratory/Skin Sensitization

May cause an allergic skin reaction

### Serious Eye Damage/Irritation

Causes eye irritation

### Skin Corrosion/Irritation

Causes skin irritation

### Specific Target Organ Toxicity - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure

### Specific Target Organ Toxicity - Single Exposure

May cause respiratory irritation

### Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

### Potential Health Effects - Miscellaneous

#### 0064742-88-7 MEDIUM MINERAL SPIRITS

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. This substance may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, lungs, reproductive system, skin. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

#### 0064742-95-6 AROMATIC HYDROCARBON MIXTURE >C9

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

#### 0000095-63-6 1,2,4-TRIMETHYLBENZENE

LC50 (rat): 18 g/m3 (4-hour exposure) (1)

LD50 (oral, rat): 5 g/kg (1)

#### 0000108-67-8 MESITYLENE

LC50 (rat): 24 g/m3 (4-hour exposure) (2)

## SECTION 12) ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life

Harmful to aquatic life with long lasting effects

### Persistence and Degradability

No data available.

### Bioaccumulative Potential

No data available.

### Mobility in Soil

No data available.

### Other Adverse Effects

No data available.

## SECTION 13) DISPOSAL CONSIDERATIONS

### Waste Disposal

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

## SECTION 14) TRANSPORT INFORMATION



	U.S. DOT Information	IMDG Information	IATA Information
<b>UN Number:</b> UN3532	UN1993	UN1993	UN1993
<b>Proper shipping name:</b> Polymerizing substance, liquid, stabilized, n.o.s. (Hydroxyethyl methacrylate)	Not regulated in containers 119 gallons (450 L) or less. Combustible Liquid in containers greater than 119 gallons for ground travel. (1,2,3-TRIMETHYLBENZENE, 1,2,4-TRIMETHYLBENZENE, AROMATIC HYDROCARBON MIXTURE >C9, MEDIUM MINERAL SPIRITS, MESITYLENE)	Flammable liquids, n.o.s. (1,2,3-TRIMETHYLBENZENE, 1,2,4-TRIMETHYLBENZENE, AROMATIC HYDROCARBON MIXTURE >C9, MEDIUM MINERAL SPIRITS, MESITYLENE)	Flammable liquids, n.o.s. (1,2,3-TRIMETHYLBENZENE, 1,2,4-TRIMETHYLBENZENE, AROMATIC HYDROCARBON MIXTURE >C9, MEDIUM MINERAL SPIRITS, MESITYLENE)
<b>Hazard Class:</b>	3	3	3
<b>Packaging:</b>	III	III	III
<b>Hazardous substance (RQ):</b>	No Data Available		
<b>Marine Pollutant:</b>	No Data Available	No Data Available	
<b>Note / Special Provision:</b>	No Data Available	No Data Available	No Data Available
<b>Toxic-Inhalation Hazard:</b>	No Data Available		

## SECTION 15) REGULATORY INFORMATION

### Safety, health and environmental regulations

The product has been evaluated against the following relevant regulations: U.S.A Toxic Substance Control Act (TSCA) California Proposition 65 Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312 Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313 Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

CAS	Chemical Name	% By Weight	Regulation List
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	30.00% - 60.00%	SARA312, TSCA - Toxic Substances Control Act (TSCA)
0064742-88-7	MEDIUM MINERAL SPIRITS	30.00% - 60.00%	SARA312, TSCA - Toxic Substances Control Act (TSCA)
0026636-08-8	2-PROPENOIC ACID, 2-METHYL-, POLYMER WITH ETHENYLBENZENE AND 2-ETHYLHEXYL 2-PROPENOATE	15.00% - 40.00%	SARA312, TSCA - Toxic Substances Control Act (TSCA)
0000095-63-6	1,2,4-TRIMETHYLBENZENE	1.00% - 5.00%	SARA313, SARA312, TSCA - Toxic Substances Control Act (TSCA)
0000108-67-8	MESITYLENE	0.50% - 1.50%	SARA312, TSCA - Toxic Substances Control Act (TSCA)
0000526-73-8	1,2,3-TRIMETHYLBENZENE	0.50% - 1.50%	SARA312, TSCA - Toxic Substances Control Act (TSCA)

## SECTION 16) OTHER INFORMATION

### Glossary

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service ; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL - Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT- US Department of Transportation.

## Version 2.0:

Revision Date: Feb 15, 2024

### Full text of H-Statements referred to under Section 3

H320	Causes eye irritation
H315	Causes skin irritation
H226	Flammable liquid and vapor
H332	Harmful if inhaled
H304	May be fatal if swallowed and enters airways
H303	May be harmful if swallowed
H373	May cause damage to organs through prolonged or repeated exposure
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H351	Suspected of causing cancer

---

## DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.